

Technical drawing of a reinforced concrete slab (A-A) showing dimensions, reinforcement details, and elevation markers.

**Dimensions and Elevation:**

- Overall width: 14.2
- Overall length: 34.2
- Section A-A width: 1.20
- Elevation markers: +4.10, Poz. 4.8, -2.00
- Vertical dimensions: 1.80, 0.30, 0.10, 0.12, 0.15
- Horizontal dimensions: 1.20, 0.30, 0.15, 0.10, 0.12, 0.15

**Reinforcement Details:**

- Top reinforcement: 2 x 2  $\phi 6$
- Bottom reinforcement: 2 x 2  $\phi 6$
- Vertical reinforcement:  $\phi 6 - (3+22)$
- Horizontal reinforcement:  $12 \times 22.5 = 270$
- Section A-A reinforcement: 4  $\phi 16$
- Section A-A reinforcement:  $\phi 6$

**Notes:**

- 1 -  $\phi 6$ , 2 -  $\phi 6$ , 3 -  $\phi 6$
- 4 -  $\phi 16$
- 5 -  $\phi 6$ , 6 -  $\phi 6$
- 7 -  $\phi 6$ , 8 -  $\phi 6$
- 9 -  $\phi 6$ , 10 -  $\phi 6$
- 11 -  $\phi 6$ , 12 -  $\phi 6$
- 13 -  $\phi 6$ , 14 -  $\phi 6$
- 15 -  $\phi 6$ , 16 -  $\phi 6$
- 17 -  $\phi 6$ , 18 -  $\phi 6$
- 19 -  $\phi 6$ , 20 -  $\phi 6$
- 21 -  $\phi 6$ , 22 -  $\phi 6$
- 23 -  $\phi 6$ , 24 -  $\phi 6$
- 25 -  $\phi 6$ , 26 -  $\phi 6$
- 27 -  $\phi 6$ , 28 -  $\phi 6$
- 29 -  $\phi 6$ , 30 -  $\phi 6$
- 31 -  $\phi 6$ , 32 -  $\phi 6$
- 33 -  $\phi 6$ , 34 -  $\phi 6$
- 35 -  $\phi 6$ , 36 -  $\phi 6$
- 37 -  $\phi 6$ , 38 -  $\phi 6$
- 39 -  $\phi 6$ , 40 -  $\phi 6$
- 41 -  $\phi 6$ , 42 -  $\phi 6$
- 43 -  $\phi 6$ , 44 -  $\phi 6$
- 45 -  $\phi 6$ , 46 -  $\phi 6$
- 47 -  $\phi 6$ , 48 -  $\phi 6$
- 49 -  $\phi 6$ , 50 -  $\phi 6$
- 51 -  $\phi 6$ , 52 -  $\phi 6$
- 53 -  $\phi 6$ , 54 -  $\phi 6$
- 55 -  $\phi 6$ , 56 -  $\phi 6$
- 57 -  $\phi 6$ , 58 -  $\phi 6$
- 59 -  $\phi 6$ , 60 -  $\phi 6$
- 61 -  $\phi 6$ , 62 -  $\phi 6$
- 63 -  $\phi 6$ , 64 -  $\phi 6$
- 65 -  $\phi 6$ , 66 -  $\phi 6$
- 67 -  $\phi 6$ , 68 -  $\phi 6$
- 69 -  $\phi 6$ , 70 -  $\phi 6$
- 71 -  $\phi 6$ , 72 -  $\phi 6$
- 73 -  $\phi 6$ , 74 -  $\phi 6$
- 75 -  $\phi 6$ , 76 -  $\phi 6$
- 77 -  $\phi 6$ , 78 -  $\phi 6$
- 79 -  $\phi 6$ , 80 -  $\phi 6$
- 81 -  $\phi 6$ , 82 -  $\phi 6$
- 83 -  $\phi 6$ , 84 -  $\phi 6$
- 85 -  $\phi 6$ , 86 -  $\phi 6$
- 87 -  $\phi 6$ , 88 -  $\phi 6$
- 89 -  $\phi 6$ , 90 -  $\phi 6$
- 91 -  $\phi 6$ , 92 -  $\phi 6$
- 93 -  $\phi 6$ , 94 -  $\phi 6$
- 95 -  $\phi 6$ , 96 -  $\phi 6$
- 97 -  $\phi 6$ , 98 -  $\phi 6$
- 99 -  $\phi 6$ , 100 -  $\phi 6$

Hand-drawn structural drawing of a reinforced concrete wall. The drawing includes a main elevation view with dimensions and reinforcement details, and two cross-sections labeled B-B and C-C.

**Main Elevation View:**

- Overall height: 4.22
- Base width: 0.40
- Top width: 0.50
- Reinforcement: 1A x 6, 2 x 4 #20, 3 #4
- Dimensions: 3 x 10 = 30, 4 x 25 = 100, 6 x 15 = 90, 3 x 10 = 30, 4 x 25 = 100, 6 x 15 = 90
- Reinforcement: 2 #14 #6, 2 #14 #6
- Dimensions: 3.40, 0.12, 0.10

**Cross-section B-B:**

- Width: 0.40
- Height: 0.30
- Reinforcement: 4 #20, 3 #4

**Cross-section C-C:**

- Width: 0.30
- Height: 0.25
- Reinforcement: 2 #20, 2 #25, 2 #20

**Detail:**




- Reinforcement: 2 #14 #6
- Dimensions: 3.40, 0.12, 0.10

Technical drawing of a reinforced concrete slab (Poz. 4.5) showing plan and section views. The plan view shows a rectangular slab with dimensions 30x60. It includes reinforcement details: top bars (2x2  $\phi 16$ ), bottom bars (2x2  $\phi 16$ ), and stirrups ( $\phi 6$ ). The section view shows the slab thickness of 25 and the reinforcement layout. The drawing is labeled "Poz. 4.5" and includes a scale of 1:25.

BETON	B 25
STAL A-II	18G2
STAL A-O	50S

Technical drawing of a beam cross-section. The drawing shows a rectangular beam with a width of 22.5 and a height of 50. The reinforcement details are as follows:

- Top reinforcement: 2 bars, 16 diameter (2 16), with a spacing of 132.
- Bottom reinforcement: 2 bars, 16 diameter (2 16), with a spacing of 132.
- Side reinforcement: 2 bars, 16 diameter (2 16), with a spacing of 132.
- Stirrups: 2 bars, 16 diameter (2 16), with a spacing of 132.
- Dimensions: The total width is 22.5, and the total height is 50. The spacing between the reinforcement bars is 132.

	PRACOWNIA PROJEKTOWA KATOWICE, PÓŁNOCNA 10		VARICOM	
	MIĘSTO ŻYWIEC ŻYWIEC, RYNEK 2			
INWESTOR	OBIEKT: SALA SPORTOWA 3. PRZEMIANA SPOŁECZNA O DOKŁADNĄ PRZYGŁĄDANIE NR 1 W ŻYWIEC		TEMAT SZTUKA SZK + SP4, S1 SP4	KODZŁY PROJEKTU WYKONAWCZY BRANŻA KONSTRUKCYJNA SKALA 1:20
PROJEKTOWAŁ mgr inż. EWA PAPAJ			DATA	NR PR.
SPRACOWAŁ mgr inż. TERESA G. JARZĄB			GRUDZIEŃ 2005	24